

NN-65C-HG-R2BD-V2



4-port Next Generation PerforMax™ sector antenna, 4x 698–896, 65° HPBW, 2x RETs

- Superior patterns for enhanced interference mitigation resulting in improved SINR, higher throughput, and more capacity
- Antenna optimized for higher gain with superior radiation efficiency
- Best in class PIM immunity
- Internal SBTs allow remote RET control from the radio over the RF jumper cable
- Powered by Andrew's SEED® technology (Sustainable Energy Efficient Design)
- Interleaved dipole technology results into an attractive, low wind load mechanical package
- The low band array is internally diplexed for an independent tilt at 700 MHz and 850 MHz

General Specifications

Antenna Type	Sector with internal RET and bias tee
Band	Single band
Color	Light Gray (RAL 7035)
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	Fiberglass, UV resistant
Radiator Material	Aluminum
Reflector Material	Aluminum
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, low band	4
RF Connector Quantity, total	4

Remote Electrical Tilt (RET) Information

RET Hardware	CommRET v2
RET Interface	8-pin DIN Female 8-pin DIN Male
RET Interface, quantity	1 female 1 male
Input Voltage	10–30 Vdc
Internal Bias Tee	Port 1
Internal RET	Low band (2)
Power Consumption, active state, maximum	10 W



NN-65C-HG-R2BD-V2

Power Consumption, idle state, maximum	2 W
Protocol	3GPP/AISG 2.0

Dimensions

Width	640 mm 25.197 in
Depth	235 mm 9.252 in
Length	2438 mm 95.984 in
Net Weight, without mounting kit	68 kg 149.914 lb

Array Layout



Array ID	Frequency (MHz)	RF Connector	RET (SRET)	AISG No.	SBT RF PORT	SBT No.	RET UID
R1	698-798	1 - 2	1	AISG1	1	1	CPxxxxxxxxxxxxxxR1
R2	824-894	1 - 2	2	AISG1			CPxxxxxxxxxxxxxxR2
R3	698-798	3 - 4	1	AISG1			CPxxxxxxxxxxxxxxR1
R4	824-894	3 - 4	2	AISG1			CPxxxxxxxxxxxxxxR2

(Sizes of colored boxes are not true depictions of array sizes)

Port Configuration

NN-65C-HG-R2BD-V2



Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	698 – 896 MHz
Polarization	±45°
Total Input Power, maximum	400 W @ 50 °C

Electrical Specifications

	R1,R2	R1,R2
Frequency Band, MHz	698–798	824–894
RF Port	1-4	1-4
Gain, Maximum, dBi	16.3	16.4
Gain, dBi	15.9	16.2
Beamwidth, Horizontal, degrees	63	60
Beamwidth, Vertical, degrees	8.9	8.1
Beam Tilt, degrees	0–10	0–10
USLS (First Lobe), dB	15	15
Front-to-Back Ratio at 180°, dB	32	33

NN-65C-HG-R2BD-V2

CPR at Boresight, dB	20	18
Isolation, Cross Polarization, dB	25	25
Isolation, Inter-band, dB	25	25
VSWR Return loss, dB	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153
Input Power per Port at 50°C, maximum, watts	150	150

Mechanical Specifications

Wind Loading @ Velocity, frontal	986.0 N @ 150 km/h (221.7 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	291.0 N @ 150 km/h (65.4 lbf @ 150 km/h)
Wind Loading @ Velocity, maximum	1,256.0 N @ 150 km/h (282.4 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	616.0 N @ 150 km/h (138.5 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

Packaging and Weights

Width, packed	752 mm 29.606 in
Depth, packed	382 mm 15.039 in
Length, packed	3201 mm 126.024 in
Weight, gross	105 kg 231.485 lb

Regulatory Compliance/Certifications

Agency	Classification
UK-ROHS	Compliant

Included Products

BSAMNT-9	–	Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.
BSAMNT-M9	–	Middle Downtilt Mounting Kit for Long Antennas for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor bracket set.

* Footnotes

Performance Note	Severe environmental conditions may degrade optimum performance
------------------	---

BSAMNT-9



Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

Product Classification

Product Type Downtilt mounting kit

General Specifications

Application Outdoor

Color Silver

Dimensions

Compatible Diameter, maximum 115 mm | 4.528 in

Compatible Diameter, minimum 60 mm | 2.362 in

Material Specifications

Material Type Galvanized steel

Packaging and Weights

Included Brackets | Hardware

Packaging quantity 1


Weight, gross 9.7 kg | 21.385 lb

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



BSAMNT-M9



Middle Downtilt Mounting Kit for Long Antennas for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor bracket set.

Product Classification

Product Type Downtilt mounting kit

General Specifications

Application Outdoor

Color Silver

Dimensions

Compatible Diameter, maximum 115 mm | 4.528 in

Compatible Diameter, minimum 60 mm | 2.362 in

Material Specifications

Material Type Galvanized steel

Packaging and Weights

Included Brackets | Hardware

Packaging quantity 1

Weight, gross 7.5 kg | 16.535 lb

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant

BSAMNT-M9

UK-ROHS

Compliant

