

# HFDC-24FIBER-P24M



## HELIAX® Fiber Distribution Closure 24 fibers Multi Mode

HELIAX® Fiber Distribution Closure 24 fibers Multi Mode.2 HMFOC 12 fibers + additional 2 entries

### Product Classification

Regional Availability	China   EMEA   Europe   India   Latin America   Middle East/Africa   North America
Product Type	Fiber distribution closure
Product Brand	HELIAX®

### General Specifications

Application	Used as a fiber junction box
Total Fiber Adapters	12
Color	Black
Doors, quantity	2
Mounting	Pipe, 44–114 mm (1.75–4.5 in) OD   Wall
Total Fibers, quantity	24
Total Ports, quantity	12

### Dimensions

Height	370 mm   14.567 in
Width	214 mm   8.425 in
Depth	118 mm   4.646 in
Jumper Breakout Length, Maximum	85 mm   3.346 in
Jumper Outlet, Quantity, Maximum	12
Jumper Outlet Diameter, Minimum	0 mm   0 in
Jumper Outlet Diameter, Maximum	7 mm   0.276 in
Trunk Entry, Diameter, Minimum	5.5 mm   0.217 in
Trunk Entry, Diameter, Maximum	17.5 mm   0.689 in
Trunk Entry, Quantity, Maximum	4

# HFDC-24FIBER-P24M

---

## Material Specifications

**Material Type** High-impact polycarbonate, UV resistant

## Mechanical Specifications

**Impact Test Method** EN62262 | IEC62262: IK07

## Environmental Specifications

**Operating Temperature** -40 °C to +75 °C (-40 °F to +167 °F)

**Qualification Standards** IEC 60529, IP68

## Packaging and Weights

**Included** Mounting kit

**Weight, net** 2.88 kg | 6.349 lb