V54-001-01-A0-E



2-port Venue Antenna, 3300-4000 MHz, 54° HPBW, Fixed Tilt

- Designed with CleanBeam[™] technology
- Sharp Roll-Off, 2T2R MetaLens™ antenna
- Supports 2x2 MIMO
- 54° Azimuth and 54° Elevation Beamwidth

General Specifications

Color White

Grounding Type RF connector inner conductor and body grounded to reflector and mounting bracket

Radome Material FRP, UV resistant

RF Connector Interface 4.3-10 Female

RF Connector Quantity, total 2

Dimensions

 Width
 299 mm | 11.772 in

 Depth
 226 mm | 8.898 in

 Length
 299 mm | 11.772 in

 Net Weight, without mounting kit
 2.7 kg | 5.952 lb

Port Configuration



V54-001-01-A0-E



Electrical Specifications

Operating Frequency Band 3300 – 4000 MHz

Polarization ±45°

Electrical Specifications

Frequency Band, MHz	3300-3800	3550-3700	3700-4000
RF Port	1,2	1,2	1,2
Gain, dBi	11.8	11.1	12.6
Beamwidth, Horizontal, degrees	53	54	40
Beamwidth, Vertical, degrees	52	54	41
USLS (First Lobe), dB	16	15	20
Front-to-Back Ratio at 180°, dB	32	32	30
Front-to-Back Ratio, Copolarization 180° ± 30°, dB	23	26	26
Isolation, Cross Polarization, dB	25	25	25
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	-153
Input Power per Port, maximum, watts	80	80	80

Packaging and Weights



V54-001-01-A0-E

 Width, packed
 390 mm | 15.354 in

 Depth, packed
 442 mm | 17.402 in

 Length, packed
 395 mm | 15.551 in

 Weight, gross
 7 kg | 15.432 lb

Regulatory Compliance/Certifications


Agency Classification
UK-ROHS Compliant

Included Products

APM40-VEN – Elevation Tilt Mounting Kit for 2.0-4.3 in (50-110 mm) OD round

members.

APM40-VEN



Elevation Tilt Mounting Kit for 2.0-4.3 in (50-110 mm) OD round members.

• Allows for adjustment of pointing angle in both azimuth and elevation

Product Classification

Product Type Downtilt and uptilt mounting kit

General Specifications

ApplicationOutdoorColorSilver

Dimensions

Compatible Diameter, maximum110 mm | 4.331 inCompatible Diameter, minimum50 mm | 1.969 inWeight, net2 kg | 4.409 lb

Packaging and Weights

Packaging quantity

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

