

# RRZZVV-65D-R6N47G



12-port sector antenna, 4x 694-960, 4x 1427-2690 and 4x 1695-2690 MHz, 65° HPBW, 6x RET

- Innovative aerodynamic shape optimized for reduced wind loading in every direction
- Reduces the amount of aluminum used to minimize CO2 release
- SEED® antenna providing high gain and improved efficiency
- High radiation and pattern efficiency for improved coverage area, capacity or reduced power consumption for a given area
- Retractable tilt indicator rods
- Includes integrated GPS (APS-XT-GPS)

## General Specifications

<b>Antenna Type</b>	Sector
<b>Band</b>	Multiband
<b>Grounding Type</b>	RF connector inner conductor and body grounded to reflector and mounting bracket
<b>Performance Note</b>	Outdoor usage
<b>RF Connector Interface</b>	4.3-10 Female
<b>RF Connector Location</b>	Bottom
<b>RF Connector Quantity, mid band</b>	8
<b>RF Connector Quantity, low band</b>	4
<b>RF Connector Quantity, total</b>	12

## Remote Electrical Tilt (RET) Information

<b>RET Hardware</b>	CommRET v2
<b>RET Interface</b>	8-pin DIN Female   8-pin DIN Male
<b>RET Interface, quantity</b>	2 female   2 male
<b>Input Voltage</b>	10-30 Vdc
<b>Internal RET</b>	Low band (2)   Mid band (4)
<b>Power Consumption, active state, maximum</b>	10 W
<b>Power Consumption, idle state, maximum</b>	2 W
<b>Protocol</b>	3GPP/AISG 2.0 (Single RET)


## Dimensions

<b>Width</b>	468 mm   18.425 in
--------------	--------------------

# RRZZVV-65D-R6N47G

<b>Depth</b>	228 mm   8.976 in
<b>Length</b>	2769 mm   109.016 in
<b>Net Weight, without mounting kit</b>	42 kg   92.594 lb

## Array Layout



Array ID	Frequency (MHz)	RF Connector	RET (SRET)	AISG No.	RET UID
R1	694-960	1 - 2	1	AISG1or2	CPxxxxxxxxxxxxxxxxR1
R2	694-960	3 - 4	2	AISG1or2	CPxxxxxxxxxxxxxxxxR2
Y1	1695-2690	5 - 6	3	AISG1or2	CPxxxxxxxxxxxxxxxxY1
Y2	1427-2690	7 - 8	4	AISG1or2	CPxxxxxxxxxxxxxxxxY2
Y3	1427-2690	9 - 10	5	AISG1or2	CPxxxxxxxxxxxxxxxxY3
Y4	1695-2690	11 - 12	6	AISG1or2	CPxxxxxxxxxxxxxxxxY4

(Sizes of colored boxes are not true depictions of array sizes)

## Port Configuration



# RRZZVV-65D-R6N47G

Logo Image



## Electrical Specifications

<b>Impedance</b>	50 ohm
<b>Operating Frequency Band</b>	1427 – 2690 MHz   1695 – 2690 MHz   694 – 960 MHz
<b>Polarization</b>	±45°
<b>Total Input Power, maximum</b>	1,800 W @ 50 °C

## Electrical Specifications

	<b>R1,R2</b>	<b>R1,R2</b>	<b>R1,R2</b>	<b>Y2,Y3</b>	<b>Y2,Y3</b>	<b>Y2,Y3</b>	<b>Y2,Y3</b>	<b>Y2,Y3</b>
<b>Frequency Band, MHz</b>	<b>698–806</b>	<b>790–894</b>	<b>890–960</b>	<b>1427–1518</b>	<b>1695–1995</b>	<b>1920–2300</b>	<b>2300–2500</b>	<b>2490–2690</b>
<b>RF Port</b>	1,2,3,4	1,2,3,4	1,2,3,4	7,8,9,10	7,8,9,10	7,8,9,10	7,8,9,10	7,8,9,10
<b>Gain at Mid Tilt, dBi</b>	16.5	17.2	17.4	17.1	18.3	19.1	19.6	20.1
<b>Beamwidth, Horizontal, degrees</b>	72	68	66	64	69	64	62	54
<b>Beamwidth, Vertical, degrees</b>	7.5	6.8	6.2	7.2	5.8	5.2	4.7	4.4
<b>Beam Tilt, degrees</b>	2–12	2–12	2–12	2–12	2–12	2–12	2–12	2–12
<b>USLS (First Lobe), dB</b>	18	17	15	16	16	15	18	17
<b>Front-to-Back Ratio at 180°, dB</b>	32	32	32	30	37	38	37	40
<b>Front-to-Back Total Power at 180° ± 30°, dB</b>	21	23	22	22	28	30	29	29
<b>CPR at Boresight, dB</b>	23	27	24	22	22	20	17	19
<b>Isolation, Cross Polarization, dB</b>	25	25	25	25	25	25	25	25
<b>Isolation, Inter-band, dB</b>	25	25	25	25	25	25	25	25
<b>VSWR   Return loss, dB</b>	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0

# RRZZVV-65D-R6N47G

<b>PIM, 3rd Order, 2 x 20 W, dBc</b>	-153	-153	-153	-153	-153	-153	-153	-153
<b>Input Power per Port at 50°C, maximum, watts</b>	300	300	300	250	250	250	200	200

## Electrical Specifications

	<b>Y1,Y4</b>	<b>Y1,Y4</b>	<b>Y1,Y4</b>	<b>Y1,Y4</b>
<b>Frequency Band, MHz</b>	<b>1695–1995</b>	<b>1920–2300</b>	<b>2300–2500</b>	<b>2490–2690</b>
<b>RF Port</b>	5,6,11,12	5,6,11,12	5,6,11,12	5,6,11,12
<b>Gain at Mid Tilt, dBi</b>	17.9	18.6	19.3	20
<b>Beamwidth, Horizontal, degrees</b>	73	70	65	57
<b>Beamwidth, Vertical, degrees</b>	5.9	5.3	4.7	4.4
<b>Beam Tilt, degrees</b>	2–12	2–12	2–12	2–12
<b>USLS (First Lobe), dB</b>	17	17	18	18
<b>Front-to-Back Ratio at 180°, dB</b>	36	34	36	37
<b>Front-to-Back Total Power at 180° ± 30°, dB</b>	28	28	26	25
<b>CPR at Boresight, dB</b>	22	22	18	20
<b>Isolation, Cross Polarization, dB</b>	25	25	25	25
<b>Isolation, Inter-band, dB</b>	25	25	25	25
<b>VSWR   Return loss, dB</b>	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
<b>PIM, 3rd Order, 2 x 20 W, dBc</b>	-153	-153	-153	-153
<b>Input Power per Port at 50°C, maximum, watts</b>	250	250	200	200

## Mechanical Specifications

<b>BASTA Version, mechanical</b>	BASTA v12
<b>Wind Loading @ Velocity, frontal</b>	547.0 N @ 150 km/h (123.0 lbf @ 150 km/h)
<b>Wind Loading @ Velocity, lateral</b>	470.0 N @ 150 km/h (105.7 lbf @ 150 km/h)
<b>Wind Loading @ Velocity, maximum</b>	976.0 N @ 150 km/h (219.4 lbf @ 150 km/h)
<b>Wind Loading @ Velocity, rear</b>	583.0 N @ 150 km/h (131.1 lbf @ 150 km/h)
<b>Wind Speed, maximum</b>	241 km/h (150 mph)

## Packaging and Weights

<b>Width, packed</b>	566 mm   22.283 in
----------------------	--------------------

# RRZZVV-65D-R6N47G

---

<b>Depth, packed</b>	380 mm   14.961 in
<b>Length, packed</b>	3001 mm   118.15 in
<b>Weight, gross</b>	57 kg   125.663 lb

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
UK-ROHS	Compliant


## Included Products

BSAMNT-2F	–	Mounting bracket for cylindrical pipe installations (60-115mm pipe diameter) for fix mechanical tilt applications.
-----------	---	--

## \* Footnotes

<b>Performance Note</b>	Severe environmental conditions may degrade optimum performance
-------------------------	---

# BSAMNT-2F



Mounting bracket for cylindrical pipe installations (60-115mm pipe diameter) for fix mechanical tilt applications.

## Product Classification

**Product Type** Fixed tilt mounting kit

## General Specifications

**Application** Outdoor

**Color** Silver

## Dimensions

**Compatible Diameter, maximum** 115 mm | 4.528 in

**Compatible Diameter, minimum** 60 mm | 2.362 in

**Weight, net** 3.8 kg | 8.378 lb

## Material Specifications

**Material Type** Galvanized steel

## Packaging and Weights

**Included** Brackets | Hardware

**Packaging quantity** 1

**Weight, gross** 4 kg | 8.818 lb

## Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.andrew.com/ProductCompliance">www.andrew.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant

# BSAMNT-2F

---

