



MR2118 Indoor Coverage and High Speed Data Enhancer for 2100 MHz UMTS and 2100 MHz LTE Applications

Product Classification

Product Type

RF repeater unit

General Specifications

Antenna Interface at Repeater

SMA Female

Indoor Antenna

Optional, not included

Optional Antenna Gain

2 dBi

Optional Antenna Type

Omni

Performance Note

Values typical, unless otherwise stated

Supervision/Control Option

Heartbeat via SMS | Remote control

Dimensions

Height

240 mm | 9.449 in

Width

240 mm | 9.449 in

Depth

35 mm | 1.378 in

Optional Antenna Length

90 mm | 3.543 in

Electrical Specifications

Gain, typical

75 dB

Gain Adjustment Range

30 dB

License Band

LTE 2100 | UMTS 2100

Local Power

6 Vdc

Mains Power

100–240 Vac

Return Loss

10 dB

Power Consumption

20 W

Electrical Specifications, Rx (Uplink)

Operating Frequency Band

1920 – 1980 MHz

Output Power @ One Carrier	18 dBm
Output Power @ Two Carriers	15 dBm
Output Power Note	Possible slight degradation of LTE requirement unwanted emission limit at certain passband adjustments and carrier constellation

Electrical Specifications, Tx (Downlink)

Operating Frequency Band	2110 – 2170 MHz (AWS 1700)
Output Power @ One Carrier	18 dBm
Output Power @ Two Carriers	15 dBm

Environmental Specifications

Operating Temperature	+5 °C to +40 °C (+41 °F to +104 °F)
Ingress Protection Test Method	IEC 60529:2001, IP30

Packaging and Weights

Weight, net	1.5 kg 3.307 lb
-------------	-------------------

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

