

# FF-65C-R2



4-port sector antenna, 4x 617–894 MHz, 65° HPBW, 2x RET, 600MHz-Ready Antenna Technology

- 4.3-10 connector significantly improves PIM consistency and smaller footprint on antenna bottom

## General Specifications

Antenna Type	Sector
Band	Single band
Color	Light Gray (RAL 7035)
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	Fiberglass, UV resistant
Radiator Material	Low loss circuit board
Reflector Material	Aluminum
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, high band	0
RF Connector Quantity, mid band	0
RF Connector Quantity, low band	4
RF Connector Quantity, total	4

## Remote Electrical Tilt (RET) Information


RET Hardware	CommRET v2
RET Interface	8-pin DIN Female   8-pin DIN Male
RET Interface, quantity	1 female   1 male
Input Voltage	10–30 Vdc
Internal RET	Low band (2)
Power Consumption, active state, maximum	10 W
Power Consumption, idle state, maximum	2 W
Protocol	3GPP/AISG 2.0 (Single RET)

# FF-65C-R2

## Dimensions

Width	498 mm   19.606 in
Depth	197 mm   7.756 in
Length	2438 mm   95.984 in
Net Weight, without mounting kit	39.8 kg   87.744 lb

## Array Layout



## Port Configuration



## Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	617 – 894 MHz

# FF-65C-R2

Polarization	±45°
Total Input Power, maximum	700 W @ 50 °C

## Electrical Specifications

Frequency Band, MHz	617–698	698–894
Gain, dBi	15	15.6
Beamwidth, Horizontal, degrees	66	56
Beamwidth, Vertical, degrees	10.2	8.6
Beam Tilt, degrees	2–13	2–13
USLS (First Lobe), dB	18	17
Front-to-Back Ratio at 180°, dB	28	30
CPR at Boresight, dB	18	18
Isolation, Cross Polarization, dB	25	25
Isolation, Inter-band, dB	25	25
VSWR   Return loss, dB	1.5   14.0	1.5   14.0
PIM, 3rd Order, 2 x 20 W, dBc	-150	-150
Input Power per Port at 50°C, maximum, watts	250	250

## Mechanical Specifications

Wind Loading @ Velocity, frontal	954.0 N @ 150 km/h (214.5 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	331.0 N @ 150 km/h (74.4 lbf @ 150 km/h)
Wind Loading @ Velocity, maximum	1,235.0 N @ 150 km/h (277.6 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	785.0 N @ 150 km/h (176.5 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

## Packaging and Weights

Width, packed	565 mm   22.244 in
Depth, packed	368 mm   14.488 in
Length, packed	2624 mm   103.307 in
Weight, gross	60.6 kg   133.6 lb

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value

# FF-65C-R2

---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.andrew.com/ProductCompliance">www.andrew.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant/Exempted



## Included Products

BSAMNT-3	–	Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.
BSAMNT-M	–	Middle Downtilt Mounting Kit for Long Antennas for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor bracket set.

## \* Footnotes

<b>Performance Note</b>	Severe environmental conditions may degrade optimum performance
-------------------------	---