

760240957 | 30" Pole Cab with Round Shaft



Bottom of the Pole, 30in Square 4G/5G capable Concealment Enclosure to house and conceal multiple low to high power radios and any other wireless infrastructure equipment in a cabinet at the base of the pole.

- Intended to house and conceal multiple radios and any other wireless infrastructure equipment in a cabinet at the base of the pole
- Flexible configuration accepts low to high-power single or dual band radios, Integrated AC load center/OVP and Disconnect and integrated AC/DC rectifier options

Available with Pole Top concealment, mmWave 5G mounting, luminaire arms.

Available After Market Kits -- ordered separately:

- 860665491-AMK-001 - Ericsson 4480/4415/8863 Radios & 6304 PSU Mounting Kit
- 860665491-AMK-003 - Custom SETAR Configuration
- 860665491-AMK-004 - Ericsson 8843/4449/4478/4890/4490& 630x PSU Mounting Kit - RETROFIT
- 860665491-AMK-006 - Nokia to Ericsson RETROFIT kit

Product Classification

Product Type	Pole cab
Product Brand	Metro Cell
Ordering Note	ANDREW® standard product with terms
Warranty	One year

General Specifications

Color	Light Gray (RAL 7035)
Color Options	Beige-Grey (RAL 7006) Black (RAL 9005) Black Green (RAL 6012) Brown (RAL 8014) Faux Concrete Silver Umbra Grey (RAL 7022)
Compatible Foundation Type	Poured Concrete Pre-Cast Concrete
Compatible Smart Devices	Cameras Digital Signage Emergency Call Station Environmental Monitoring Security Lighting WIF
Cooling	Fan Cooling
Power Supply Compatibility	6302 6304 6308 ABB CC1600 DELTA 2.0 PSU-AC-08
Radio Compatibility, Ericsson	1281 220x 440x 4415 4449 4455 4461 4471 4478 4480 4490 4890 63
Radio Compatibility, Nokia	(2) Aircscale dual band radios (160W or 320W and (2) Delta 1kW rectifiers (base) AHFIA AHFIB AHLBBA
Radio Compatibility Samsung	AT1K01 AT1K02 AT1K0X Diplexer RF4402D-D1A RFV01U-D1A RFV01U-D2A RT2201-46A
Radios Included	None

Dimensions

760240957 | 30" Pole Cab with Round Shaft

Height Note	4 ft tall Equipment Cabinet Base
Pole Height Options	10.668 m 35 ft 12.192 m 40 ft 6.096 m 20 ft 7.62 m 25 ft 9.144 m 30 ft
Width	762 mm 30 in
Depth	762 mm 30 in
Depth Note	Square
Pole Diameter	203.2 mm 8 in

Electrical Specifications

Input Voltage	230–115 Vac
Generator Connection	No connection
Power/Fiber Input	AC load center with OVP and disconnect

Material Specifications

Finish Aluminum	Chromate
Finish Concealment Covers	Powder coated
Material Type	Steel

Environmental Specifications

Thermal Compliance	GR-487
--------------------	--------