


# SHP1-23/B

Base Product



0.3 m | 1 ft Sentinel® High Performance Antenna, single-polarized, 21.200–23.600 GHz

Alternative products available:

SHPX1-23/B      0.3 m | 1 ft Sentinel® High Performance Antenna, dual-polarized, 21.200–23.600 GHz

## Product Classification

|               |                   |
|---------------|-------------------|
| Product Type  | Microwave antenna |
| Product Brand | Sentinel®         |

## General Specifications

|                       |                                                            |
|-----------------------|------------------------------------------------------------|
| Antenna Type          | SHP - Sentinel® High Performance Antenna, single-polarized |
| Polarization          | Single                                                     |
| Side Struts, Included | 0                                                          |
| Side Struts, Optional | 0                                                          |

## Dimensions

|                   |              |
|-------------------|--------------|
| Diameter, nominal | 0.3 m   1 ft |
|-------------------|--------------|

## Electrical Specifications

|                                                  |                     |
|--------------------------------------------------|---------------------|
| Operating Frequency Band                         | 21.200 – 23.600 GHz |
| Gain, Low Band                                   | 35.2 dBi            |
| Gain, Mid Band                                   | 35.6 dBi            |
| Gain, Top Band                                   | 36 dBi              |
| Boresite Cross Polarization Discrimination (XPD) | 30 dB               |
| Front-to-Back Ratio                              | 66 dB               |

# SHP1-23/B

---


|                                                               |                                                                                            |
|---------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Beamwidth, Horizontal                                         | 2.9 °                                                                                      |
| Beamwidth, Vertical                                           | 2.9 °                                                                                      |
| Return Loss                                                   | 17.7 dB                                                                                    |
| VSWR                                                          | 1.3                                                                                        |
| Radiation Pattern Envelope Reference (RPE)                    | 7275B                                                                                      |
| Electrical Compliance                                         | Brazil Anatel Class 2   Canada SRSP 321.8 Part B   ETSI 302 217 Class 4   US FCC Part 101A |
| Cross Polarization Discrimination (XPD) Electrical Compliance | ETSI EN 302217 XPD Category 2                                                              |

## Mechanical Specifications

|                                   |                              |
|-----------------------------------|------------------------------|
| Compatible Mounting Pipe Diameter | 50 mm–115 mm   2.0 in–4.5 in |
| Fine Azimuth Adjustment Range     | ±15°                         |
| Fine Elevation Adjustment Range   | ±15°                         |
| Wind Speed, operational           | 201 km/h   124.896 mph       |
| Wind Speed, survival              | 250 km/h   155.343 mph       |

# SHP1-23/B

## Antenna Dimensions and Mounting Information



| Dimension in Inches(mm) |           |           |           |           |
|-------------------------|-----------|-----------|-----------|-----------|
| Antenna size, ft(m)     | A         | B         | C         | D         |
| 1(0.3)                  | 15.3(389) | 11.3(287) | 12.8(326) | 12.6(319) |

## Wind Forces at Wind Velocity Survival Rating

|                                              |                           |
|----------------------------------------------|---------------------------|
| <b>Axial Force (FA)</b>                      | 446 N   100.265 lbf       |
| <b>Angle <math>\alpha</math> for MT Max</b>  | 0 °                       |
| <b>Side Force (FS)</b>                       | 222 N   49.908 lbf        |
| <b>Twisting Moment (MT)</b>                  | 144 N-m   1,274.507 in lb |
| <b>Zcg without Ice</b>                       | 74 mm   2.913 in          |
| <b>Zcg with 1/2 in (12 mm) Radial Ice</b>    | 111 mm   4.37 in          |
| <b>Weight with 1/2 in (12 mm) Radial Ice</b> | 19 kg   41.888 lb         |

# SHP1-23/B

## Wind Forces at Wind Velocity Survival Rating Image



## Packaging and Weights

**Weight, net**

6 kg | 13.228 lb

## Regulatory Compliance/Certifications

### Agency

ISO 9001:2015

### Classification

Designed, manufactured and/or distributed under this quality management system

## \* Footnotes

### Operating Frequency Band

Bands correspond with CCIR recommendations or common allocations used throughout the world. Other ranges can be accommodated on special order.

# SHP1-23/B

---

## **Gain, Mid Band**

For a given frequency band, gain is primarily a function of antenna size. The gain of Andrew antennas is determined by either gain by comparison or by computer integration of the measured antenna patterns.

## **Boresite Cross Polarization Discrimination (XPD)**

The difference between the peak of the co-polarized main beam and the maximum cross-polarized signal over an angle twice the 3 dB beamwidth of the co-polarized main beam.

## **Front-to-Back Ratio**

Denotes highest radiation relative to the main beam, at  $180^\circ \pm 40^\circ$ , across the band. Production antennas do not exceed rated values by more than 2 dB unless stated otherwise.

## **Return Loss**

The figure that indicates the proportion of radio waves incident upon the antenna that are rejected as a ratio of those that are accepted.

## **VSWR**

Maximum; is the guaranteed Peak Voltage-Standing-Wave-Ratio within the operating band.

## **Radiation Pattern Envelope Reference (RPE)**

Radiation patterns define an antenna's ability to discriminate against unwanted signals. Under still dry conditions, production antennas will not have any peak exceeding the current RPE by more than 3dB, maintaining an angular accuracy of  $\pm 1^\circ$  throughout

## **Cross Polarization Discrimination (XPD) Electrical Compliance**

The difference between the peak of the co-polarized main beam and the maximum cross-polarized signal over an angle twice the 3 dB beamwidth of the co-polarized main beam.

## **Wind Speed, operational**

For VHLP(X), SHP(X), HX and USX antennas, the wind speed where the maximum antenna deflection is  $0.3 \times$  the 3 dB beam width of the antenna. For other antennas, it is defined as a deflection is equal to or less than 0.1 degrees.

## **Wind Speed, survival**

The maximum wind speed the antenna, including mounts and radomes, where applicable, will withstand without permanent deformation. Realignment may be required. This wind speed is applicable to antenna with the specified amount of radial ice.

## **Axial Force (FA)**

Maximum forces exerted on a supporting structure as a result of wind from the most critical direction for this parameter. The individual maximums specified may not occur simultaneously. All forces are referenced to the mounting pipe.

## **Side Force (FS)**

Maximum side force exerted on the mounting pipe as a result of wind from the most critical direction for this

**Twisting Moment (MT)**

parameter. The individual maximums specified may not occur simultaneously. All forces are referenced to the mounting pipe.

Maximum forces exerted on a supporting structure as a result of wind from the most critical direction for this parameter. The individual maximums specified may not occur simultaneously. All forces are referenced to the mounting pipe.