CLT4NM-4M-CO



MQ Multiport cluster 4 ports cable assembly with interface type MQ female to N male, size 1/4", length 4 meters

Product Classification

Product Type Wireless transmission cable assembly

Product Series MQ

General Specifications

Attachment, Connector A Factory attached

Attachment, Connector B Factory attached

Body Style, Connector A

Body Style, Connector B

Interface, Connector A

MQ Female

Interface, Connector B

N Male

Specification Sheet Revision Level

A

Dimensions

Length 4 m | 13.123 ft

Nominal Size 1/4 in

Port Configuration

Pin Assignment	Label	
1	MQ4-1 (R-)	
2	MQ4-2(CR-)	
3	MQ4-3 (CL-)	
4	MQ4-4 (L-)	

VSWR/Return Loss

Frequency Band VSWR Return Loss (dB) Insertion Loss, typical (dB)

ANDREW® an Amphenol company

CLT4NM-4M-CO

0-2700 MHz	1.151	23.1	1.98
2700-4200 MHz	1.201	20.8	2.46
4200-6000 MHz	1.352	16.5	2.94

Mechanical Specifications

Minimum Bend Radius, multiple Bends25.4 mm | 1 inMinimum Bend Radius, single Bend25.4 mm | 1 in

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C} \text{ to } +85 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +185 \,^{\circ}\text{F})$

Immersion Test Method IEC 60529, IP67

